

# FSTD No EU-A0035

S/N: FlightSafety / 8674

## Sikorsky S-92A

Located at

**FlightSafety International, Inc.**  
**Flyplassveien 180**  
**4055 Sola**  
**Norway**

### FSTD DATA SHEET

A.	Type or variant of aircraft:	Sikorsky S-92A
B.	FSTD qualification level:	HELICOPTER FFS LEVEL D
C.	Primary reference document:	CS-FSTD(H) initial issue
D.	Visual system:	FSI FVS, VITAL 1100, LCoS projectors, FOV 220degx60deg, collimated
E.	Motion system:	FSI FSS, 60 inch, electric, 6 DOF, secondary 1-axis electric vibration platform
F.	Engine fit:	General Electric GE CT7-8A
G.	Instrument fit:	According to rotorcraft type equipped with AMS 8.0
H.	ACAS fit:	TCAS I
I.	Windshear:	No profile available
J.	Additional capabilities:	None
K.	Restrictions or limitations:	None

L.	Guidance information for training, testing and checking considerations				
CAT I	RVR	500 m	DH	200 ft	yes
CAT II	RVR	300 m	DH	100 ft	n/a
CAT III (lowest minimum)	RVR	m	DH	ft	n/a
LVTO	RVR	150 m			yes
Recency					yes
IFR-training / check					yes / yes
Type rating					yes
Proficiency checks					yes
Autocoupled approach					yes
Autoland / roll out guidance					n/a / n/a
ACAS I /II					yes / n/a
Windshear warning system / predictive windshear					n/a / n/a
WX-radar					yes
HUD / HUGS					n/a / n/a
FANS					n/a
GPWS / EGPWS					n/a / yes
GPS					yes
ETOPS capability					n/a
Other:	Airborne Radar Approach (ARA), ditching, ship landing, rig landing, elevated platform landing, Search And Rescue (SAR) visual models and search patterns, Night Vision Goggle (NVG) compatible lighting / visual system, RNP APCH limited to: [LNAV, LNAV/VNAV, LPV]				