

FSTD DATA SHEET

EU-A0035

FSTD Sikorsky S-92A

S/N: FlightSafety – 8674

Located at

FlightSafety International, Inc.

Flyplassveien 180
4055 Sola
Norway

A.	Type or variant of aircraft	Sikorsky S-92A
B.	FSTD qualification level	HELICOPTER FFS LEVEL D
C.	Primary reference document	CS-FSTD(H) initial issue
D.	Visual system	FSI FVS, VITAL 1100, LCoS projectors, FOV 220degx60deg, collimated
E.	Motion system	FSI FSS, 60 inch, electric, 6 DOF, secondary 1-axis electric vibration platform
F.	Engine fit	General Electric GE CT7-8A
G.	Instrument fit	According to rotorcraft type equipped with AMS 8.0
H.	ACAS fit	TCAS II (ver. 7.1)
I.	Windshear	No profile available
J.	Additional capabilities	None
K.	Restrictions or limitations	None

L.	Guidance information for training, testing and checking considerations			
CAT I	RVR	550 m	DH 200 ft	yes
CAT II	RVR	300 m	DH 100 ft	n/a
CAT III (lowest minimum)	RVR	m	DH ft	n/a
LVTO	RVR	150 m		yes
Recency				yes
IFR-training / check				yes / yes
Type rating				yes
Proficiency checks				yes
Autocoupled approach				yes
Autoland / roll out guidance				n/a / n/a
ACAS I / II				n/a / yes
Windshear warning system / predictive windshear				n/a / n/a
WX-radar				yes
HUD / HUGS				n/a / n/a
FANS				n/a
GPWS / EGPWS				n/a / yes
ETOPS capability				n/a
GPS				yes
Other	Airborne Radar Approach (ARA), ditching, ship landing, rig landing, elevated platform landing, Search And Rescue (SAR) visual models and search patterns, Night Vision Goggle (NVG) compatible lighting / visual system, RNP APCH limited to: [LNAV, LNAV/VNAV, LPV], rig approach, external load lifting, slope landing			

Revision 6, date of issue: 8 October 2024 - EU-A0035_CERT_REV_6_20241008-DS