

FSTD No EU-DK1122

S/N: CAE – MA002NC4.01.2.899 / -

Bell 212

Located at

CAE STS Ltd.
CAE Stockholm Training Centre
Kabinvägen 5
SE-195 87 Stockholm-Arlanda
Sweden

FSTD DATA SHEET

A.	Type or variant of aircraft:	Bell 212
B.	FSTD qualification level:	HELICOPTER FFS LEVEL CG
C.	Primary reference document:	AC120-63
D.	Visual system:	CAE, Maxvue Enhanced B, CRT projectors, FOV 210degx40deg
E.	Motion system:	CAE, 60 inch, hydraulic, 6 DOF
F.	Engine fit:	Pratt & Whitney PT6T-3B
G.	Instrument fit:	According to aircraft type equipped with Garmin EFIS, GPS GTN750/650 and Roadrunner EFIS ADI/HSI AFI 4700
H.	ACAS fit:	None
I.	Windshear:	No profile available
J.	Additional capabilities:	None
K.	Restrictions or limitations:	None

L.	Guidance information for training, testing and checking considerations					
CAT I	RVR	500	m	DH	200 ft	yes
CAT II	RVR	300	m	DH	100 ft	n/a
CAT III (lowest minimum)	RVR		m	DH	ft	n/a
LVTO	RVR	150	m			n/a
Recency						yes
IFR-training / check						yes / yes
Type rating						yes
Proficiency checks						yes
Autocoupled approach						yes
Autoland / roll out guidance						n/a / n/a
ACAS I /II						n/a / n/a
Windshear warning system / predictive windshear						n/a / n/a
WX-radar						yes
HUD / HUGS						n/a / n/a
FANS						n/a
GPWS / EGPWS						n/a / n/a
GPS						yes
ETOPS capability						n/a
Other:	Night Vision Imaging System (NVIS), sling load operation, hoist operation, RNP APCH limited to: [LNAV, LNAV/VNAV, LPV]					