

FSTD DATA SHEET

EU-DK1123

FSTD Bell 412

S/N: CAE – MA002NC4.01.2.899 / -

Located at

CAE STS Ltd.

CAE Centre Stockholm AB
Kabinvägen 5
SE-190 60 Stockholm-Arlanda
Sweden

A.	Type or variant of aircraft	Bell 412
B.	FSTD qualification level	HELICOPTER FFS LEVEL CG
C.	Primary reference document	AC120-63
D.	Visual system	CAE, Maxvue Enhanced B, CRT projectors, FOV 210degx40deg
E.	Motion system	CAE, 60 inch, hydraulic, 6 DOF
F.	Engine fit	Pratt & Whitney PT6T-3B
G.	Instrument fit	According to aircraft type equipped with Garmin EFIS, GPS GTN750/650 and Roadrunner EFIS ADI/HSI AFI 4700
H.	ACAS fit	None
I.	Windshear	No profile available
J.	Additional capabilities	None
K.	Restrictions or limitations	None

L.	Guidance information for training, testing and checking considerations				
CAT I	RVR	550	m	DH 200 ft	yes
CAT II	RVR	300	m	DH 100 ft	n/a
CAT III (lowest minimum)	RVR		m	DH ft	n/a
LVTO	RVR	150	m		n/a
Recency					yes
IFR-training / check					yes / yes
Type rating					yes
Proficiency checks					yes
Autocoupled approach					yes
Autoland / roll out guidance					n/a / n/a
ACAS I / II					n/a / n/a
Windshear warning system / predictive windshear					n/a / n/a
WX-radar					yes
HUD / HUGS					n/a / n/a
FANS					n/a
GPWS / EGPWS					n/a / n/a
ETOPS capability					n/a
GPS					yes
Other	Night Vision Imaging System (NVIS), sling load operation, hoist operation, RNP APCH limited to: [LNAV, LNAV/VNAV, LPV]				

Revision 1, date of issue: 6 September 2024 - EU-DK1123_CERT_REV_1_20240906-DS