

# FSTD DATA SHEET

**EU-C0055**

**FSTD Robinson R22 Beta II**

S/N: VRMotion – VRM-SL1-3qZ6-10

Located at

**VRMotion AG**

Sonnentalstrasse 8  
8600 Dübendorf  
Switzerland

A.	Type or variant of aircraft	Robinson R22 Beta II
B.	FSTD qualification level	HELICOPTER FNPT LEVEL II
C.	Primary reference document	CS-FSTD(H) initial issue and special conditions (see Master Qualification Tests Guide, MQTG)
D.	Visual system	IPACS, Aerofly VRM, Head Mounted Display (HMD), Virtual Reality (VR), static FOV 80degx65deg
E.	Motion system	VRMotion, 32 cm, electric, 6 DOF
F.	Engine fit	Generic 145 hp piston engine (representative of Lycoming O-360-J2A), semi-rigid two-bladed main rotor
G.	Instrument fit	Standard to Robinson R22 Beta II
H.	ACAS fit	None
I.	Windshear	No profile available
J.	Additional capabilities	None
K.	Restrictions or limitations	None

L.	Guidance information for training, testing and checking considerations						
CAT I	RVR	500	m	DH	200	ft	n/a
CAT II	RVR	300	m	DH	100	ft	n/a
CAT III (lowest minimum)	RVR		m	DH		ft	n/a
LVTO	RVR	150	m				n/a
Recency							n/a
IFR-training / check							yes (partially) / n/a
Type rating							yes (partially)
Proficiency checks							n/a
Autocoupled approach							n/a
Autoland / roll out guidance							n/a / n/a
ACAS I / II							n/a / n/a
Windshear warning system / predictive windshear							n/a / n/a
WX-radar							n/a
HUD / HUGS							n/a / n/a
FANS							n/a
GPWS / EGPWS							n/a / n/a
ETOPS capability							n/a
GPS							n/a
Other	Slope landing, no RNP APCH capability						

Revision 3, date of issue: 25 April 2022 - EU-C0055\_CERT\_REV\_3\_20220425-DS